



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 1 of 10

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Product Description: HDPE without polymer processing aid, see Section 16 for applicable grades.

Intended Use: Injection Moulding

COMPANY IDENTIFICATION

Supplier: Ladtech, Inc.
6704 Meadowlark Court
Lino Lakes, MN 55038

Product Technical Information 1-810-238-2186
Supplier General Contact 1-608-269-3154

SECTION 2

COMPOSITION / INFORMATION ON INGREDIENTS

No Reportable Hazardous Substance(s) or Complex Substance(s).

NOTE: The product may contain varying levels of additives such as slip and antiblocking agents, antioxidants and stabilizers.

SECTION 3

HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

POTENTIAL PHYSICAL / CHEMICAL EFFECTS

WARNING: May form combustible dust concentrations in air (during processing/handling). Spilled pellets present a slipping hazard on hard surfaces. Contact with hot material can cause thermal burns which may result in permanent damage. Material can accumulate static charges which may cause an ignition.

POTENTIAL HEALTH EFFECTS

If dust is generated, it could scratch the eyes and cause minor irritation to the respiratory tract. When heated, the vapors/fumes given off may cause respiratory tract irritation.

NFPA Hazard ID:	Health: 1	Flammability: 1	Reactivity: 0
HMIS Hazard ID:	Health: 1	Flammability: 1	Reactivity: 0

SECTION 4

FIRST AID MEASURES

INHALATION



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 2 of 10

At ambient/normal handling temperatures, no adverse effects due to inhalation of dust are expected. In case of adverse exposure to vapors and / or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest.

SKIN CONTACT

For hot product: Immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

No adverse effects due to ingestion are expected.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Fire Fighting Instructions: Assure an extended cooling down period to prevent re-ignition. Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Explosion: Avoid generating dust; fine dust dispersed in air in sufficient concentration and in the presence of an ignition source is a potential dust explosion hazard.

Hazardous Combustion Products: Smoke, Fume, Incomplete combustion products, Oxides of carbon, Flammable hydrocarbons

FLAMMABILITY PROPERTIES

Flash Point [Method]: N/A

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/A

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 3 of 10

PROTECTIVE MEASURES

Avoid contact with spilled material. Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (for example, clearing dust surfaces with compressed air). Prevent dust exposure to ignition sources. For example, use non-sparking tools and prohibit smoking, flares, sparks or flames in immediate area. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

SPILL MANAGEMENT

Land Spill: Spilled pellets present a slipping hazard on hard surfaces. Prevent dust cloud. Small Dry Spills: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas. For Large Spills: Cover spill with plastic sheet or tarpaulin to minimize spreading.

SECTION 7

HANDLING AND STORAGE

HANDLING

Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dust from material can accumulate electrostatic charges due to friction from transfer and mixing operations and cause an electrical spark (ignition source). Provide adequate precautions to ignition sources, such as electrical grounding and bonding, inert atmosphere or non-sparking tools. However, bonding and grounds may not eliminate the hazard for static accumulation. Consult local applicable standards for guidance. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids and EN 61241, Electrical Apparatus for Use in the Presence of Combustible Dust for safe handling. Avoid elevated temperatures for prolonged periods of time. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent small spills and leakage to avoid slip hazard. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight, and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletized bags or other package units. Indeed, polymer products may be dimensionally unstable under certain conditions. Avoid conditions generating heat during transfer operations.

Loading/Unloading Temperature: [Ambient]

Transport Temperature: [Ambient]

Transport Pressure: [Ambient]



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 4 of 10

Static Accumulator: This material is a static accumulator.

STORAGE

The container choice, for example storage vessel, may effect static accumulation and dissipation. Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures. Do not store in open or unlabeled containers.

Storage Temperature: [Ambient]

Storage Pressure: [Ambient]

Suitable Containers/Packing: Bulk Containers; Hopper Cars; Bags; Boxes; Drums; Octatainer; Silos

Suitable Materials and Coatings (Chemical Compatibility): Aluminum; Polyethylene Bags

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product: For dusty conditions, OSHA recommends for particulates not otherwise regulated an 8-hour TWA of 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction); ACGIH recommends for insoluble and poorly soluble particles not otherwise specified an 8-hour TWA of 10 mg/m³ (inhalable particles), 3 mg/m³ (respirable particles). Product may also contain varying levels of additives, such as slip and antiblocking agents (talc or silica), antioxidants, stabilizers, and corrosion inhibitors. Certain grades may contain cristobalite, a form of crystalline silica, as an additive that is encapsulated in the polymer. Inhaled crystalline silica in an occupational environment is recognized as a known human carcinogen. However, the potential for release of silica to the air when this polymer is handled has been assessed and the encapsulated silica within the polymer is not expected to pose a health hazard when processed under normal conditions of use.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. **SPECIAL PRECAUTIONS:** Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures (for example, oxygenated components). Processors of this product should assure that adequate ventilation or other controls are used to control exposure. It is recommended that the current ACGIH-TLVs for thermal degradation by-products be observed. Contact your local sales representative for further information. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product are designed and maintained to minimize dust generation and accumulation. Ensure that dust-handling systems (such as exhaust ducts, dusts collectors, vessels, and processing equipment) are designed to minimize the potential for dust ignition and prevent explosion propagation. For example, use explosion relief vents, an explosion suppression system or inert equipment internals. Additional examples of proper equipment include using only appropriately classified electrical equipment and powered industrial trucks.

PERSONAL PROTECTION



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 24 Feb 2012

Page 5 of 10

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Particulate air-purifying respirator approved for dust / oil mist is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If product is hot, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If product is hot, thermally protective, chemical resistant apron and long sleeves are recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Solid

Form: Pellet, Granule,

Color: Clear to Opaque, Black to Grey

Odor: None to Mild

Odor Threshold: N/A

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 6 of 10

Relative Density: 0.94 - 0.97
Bulk Density: 0.4 g/cc at 20 °C - 1 g/cc at 20 °C
Density (at 20 °C): 940 kg/m³ (7.84 lbs/gal, 0.94 kg/dm³) - 970 kg/m³ (8.09 lbs/gal, 0.97 kg/dm³)
Flash Point [Method]: N/A
Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
Autoignition Temperature: N/A
Boiling Point / Range: N/A
Vapor Density (Air = 1): N/A
Vapor Pressure: [Negligible]
Evaporation Rate (n-butyl acetate = 1): N/A
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): N/A
Solubility in Water: Negligible
Viscosity: N/A
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: 120°C (248°F) - 140°C (284°F)
Molecular Weight: > 25000
Hygroscopic: No

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Avoid elevated temperatures for prolonged periods of time.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
Inhalation	
Toxicity: Data available.	Minimally Toxic. Based on chemical structure (polymers).
Irritation: Data available.	Negligible hazard at ambient/normal handling temperatures. Based on chemical structure (polymers).
Ingestion	
Toxicity: Data available.	Minimally Toxic. Based on chemical structure (polymers).
Skin	
Toxicity: Data available.	Minimally Toxic. Based on chemical structure (polymers).
Irritation: Data available.	Negligible irritation to skin at ambient temperatures. Based on chemical structure (polymers).



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 7 of 10

Eye	
Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on chemical structure (polymers).

CHRONIC/OTHER EFFECTS

For the product itself:

Dust may be irritating to the eyes and respiratory tract. Elevated temperatures or mechanical action may form vapors, mists or fumes which may be irritating to the eyes and respiratory tract.

Contains:

Additives that are encapsulated in the polymer. Under the normal conditions for processing and use of this polymer the encapsulated additives are not expected to pose any health hazard. However, grinding of the polymer is not recommended without the use of appropriate measures to control exposure (see Section 8 - Engineering Controls).

Additional information is available by request.

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = NTP CARC
2 = NTP SUS

3 = IARC 1
4 = IARC 2A

5 = IARC 2B
6 = OSHA CARC

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.
Material -- Not expected to be harmful to terrestrial organisms.

MOBILITY

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material -- Expected to be persistent.

Hydrolysis:

Material -- Transformation due to hydrolysis not expected to be significant.

Photolysis:

Material -- Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation:

Material -- Transformation due to atmospheric oxidation not expected to be significant.

BIOACCUMULATION POTENTIAL

Material -- Potential to bioaccumulate is low.



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 8 of 10

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

LAND (DOT): Not Regulated for Land Transport

LAND (TDG): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transport

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

Complies with the following national/regional chemical inventory requirements:: TSCA

EPCRA: This material contains no extremely hazardous substances.

CWA / OPA: Plastic pellets are defined by the US EPA under the Clean Water Act (40CFR122.26) as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 9 of 10

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

SARA (313) TOXIC RELEASE INVENTORY: This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P65 CARC	15 = MI 293	

Code key: CARC=Carcinogen; REPRO=Reproductive

Contact Sales / Marketing group for complete chemical inventory listing applicable to product.

SECTION 16 OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

- Revision Changes:
- Section 04: First Aid Inhalation was modified.
- Section 05: Fire Fighting Measures - Unusual Fire Hazards was modified.
- Section 09: Phys/Chem Properties Note was modified.
- Section 08: Comply with applicable regulations phrase was modified.
- Section 07: Handling and Storage - Handling was modified.
- Hazard Identification: Health Hazards was modified.
- Hazard Identification: Physical/Chemical Hazard was modified.
- Section 11: Dermal Lethality Test Comment was modified.
- Section 11: Oral Lethality Test Comment was modified.
- Section 11: Inhalation Lethality Test Comment was modified.
- Section 11: Dermal Irritation Test Comment was modified.
- Section 11: Eye Irritation Test Comment was modified.
- Section 07: Materials/Coatings - Suitable was modified.
- Section 06: Accidental Release - Spill Management - Land was modified.
- Section 08: Respiratory Protection was modified.
- Section 08: Exposure Control was modified.
- Section 15: List Citation Table - Header was modified.
- Section 11: Inhalation Lethality Test Comment was modified.
- Section 15: National Chemical Inventory Listing - Header was modified.
- Section 15: National Chemical Inventory Listing was modified.
- Section 16: Materials Covered was modified.
- Section 11: Chronic Tox - Component - Header was modified.
- Section 06: Protective Measures was added.
- Section 06: Accidental Release - Protective Measures - Header was added.



Product Name: HIGH DENSITY POLYETHYLENE - Grades designated by HD or HDP prefix

Revision Date: 1 January 2016

Page 10 of 10

THIS MSDS COVERS THE FOLLOWING MATERIALS: High Density PE grades for which the grade name consists of a base polymer designated by HD or HDP prefix followed by a suffix referring to an additive package. Applicable designations follow. | Base polymers : | HD 6601 | HD 6605 | HD 6704 | HD 6706 | HD 6708 | HD 6714 | HD 6719 | HD 6733 | HD 6761 | HD 6801 | HD 6908 | HD 6950 | HD 7800P | HD 7845 | HD 7925 | HD 7960 | HD 8660 | HD 8760 | HD 9850 | HD 9856 | HD9815 | HD9830 | HDP 8660 | HDP 8760 | /// List of possible additive packages | 02 | 05 | 10 | 12 | 13 | 17 | 18 | 19 | 29 | 30 | 62 | 65 | 70 | B | SE | YN | YU

PRECAUTIONARY LABEL TEXT:

Caution! Excessive exposure to dust may cause irritation of the nose and throat, and mechanical irritation of the eyes. Avoid generating dust. Use adequate ventilation under dusty conditions to keep airborne levels below recommended exposure limits. If inhaled and symptoms develop, remove to fresh air and get medical attention.

The information and recommendations contained herein are, to the best of LADTECH, INC. knowledge and belief, accurate and reliable as of the date issued. You can contact LADTECH INC to insure that this document is the most current available from LADTECH, INC. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited.